



*Quality Management System certified ISO 9001: 2015 by Intertek*

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY  
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397  
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992  
**MADE IN ITALY - UN 1263 PAINT**



**Famiglia: EDILIZIA**

## **Prodotto: PARETI VIVE**

### **DESCRIZIONE**

Idropittura lavabile-traspirante per interni caratterizzata da eccezionale potere antimuffa e anticondensa, grazie alla presenza di microsfere cave di vetro. Le proprietà termoisolanti e fonoassorbenti, riducono la dispersione di calore attraverso le pareti, impedendo la formazione di efflorescenze e muffe. Ideale come igienizzante negli ambienti interni dove  
c



*Quality Management System certified ISO 9001: 2015 by Intertek*

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY  
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397  
[www.tixepaint.com](http://www.tixepaint.com) - [mail@tixepaint.com](mailto:mail@tixepaint.com) - P.IVA 01779800992  
**MADE IN ITALY - UN 1263 PAINT**



## **DILUIZIONE**

Il prodotto è da diluire con acqua: le quantità sono relative all



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY  
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397  
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992  
**MADE IN ITALY - UN 1263 PAINT**



## Family: BUILDING



## Product: PARETI VIVE

### DESCRIPTION

Washable-breathable water-based paint for interiors characterized by exceptional anti-mold and anti-condensation power, thanks to the presence of hollow glass microspheres. The heat-insulating and sound-absorbing properties reduce the dispersion of heat through the walls, preventing the formation of efflorescence and mold. Ideal as a sanitizing in indoor environments where there is moisture caused by condensation.

**HACCP certified product, according to test report No. 378 / L dated 07/22/2019, issued by GFC Chimica. STANDARD TESTS UNI 11021: 2002.**

### MAIN FEATURES

- Excellent thermal sensation
- Excellent anti-mold effect
- Excellent applicability
- Excellent coverage
- Good washability

### USE

Used for internal walls and ceilings subjected to considerable temperature changes with the outside. Suitable for humid environments and where the proliferation of mold has been ascertained: changing rooms, showers, bathrooms, kitchens.

### APPLICATION

The surface to be painted with PARETI VIVE must be prepared with suitable treatment, namely:

**ON NEW SUPPORTS (STUCCO or MALTA):** for a better anchorage and a longer life, the surface must be free of grease or dust. Apply a coat of insulation or fixative by brush. After at least 4 hours, apply two coats of PARETI VIVE.

#### ON ALREADY PAINTED SUPPORTS:

with washable water-based paint: plaster and sand if necessary; clean the wall with a damp sponge and apply one coat with an insulating brush or fixative only on stuccoing. After at least 4 hours, apply two coats of PARETI VIVE.

With tempera, lime paints or crumbling paints: plaster and sand if necessary; clean the wall with a damp sponge, apply a coat of fixative or insulating brush over the entire surface. After at least 4 hours, apply two coats of PARETI VIVE.

**On moldy and condensation-blackened walls, remove the molds with hygienizer. Ensure the quality of the substrate that must be solid and free from smears. Proceed as described previously**

Recommended applications: brush, roller, airless, spray.

#### Environmental and support conditions:

The substrate must be dry, free of dust, grease and any other pollutant

Room temperature: min. 10 ° C / max 35 ° C

Relative humidity of the environment: <75%

Support temperature: min. 10 ° C / max 35 ° C



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY  
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397  
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992  
**MADE IN ITALY - UN 1263 PAINT**



#### **DILUTION**

The product is to be diluted with water: the quantities are related to the tool used and the type of finish desired:  
brush up to 20% by volume (1-2 hands),  
Lacquered finishing brush up to 30% by volume (3-4 hands),  
10% volume roll (1-2 hands).

**A careful mixing of the product before application is recommended, in order to guarantee the constant homogeneity of the product.**

#### **STORAGE**

Keep the tin tightly closed, protected from frost and sources of heat.

#### **PHYSICAL CHARACTERISTICS** (at 20 ° C and 50% - 60% U.R.)

Specific weight                      0.70