



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992
MADE IN ITALY - UN 1263 PAINT



Famiglia: EDILIZIA

Prodotto: ROYALFIX

DESCRIZIONE

Primer consolidante alcali-resistente ad elevata penetrazione per esterni ed interni; particolarmente indicato per tutti i supporti murali quali gesso, cartongesso, rasature a calce, intonaci civili base calce e/o cemento, pitture a base di leganti organici (Quarzi), silicati, silossani e calci; riduce ed uniforma gli assorbimenti del supporto, garantendo un perfetto ancoraggio ed uniformità di tinta delle mani successive dei prodotti di finitura.

Aspetto della pellicola essiccata: trasparente

CARATTERISTICHE PRINCIPALI

- Consolidante di sfarinamenti
- Penetrante
- Uniformante di assorbimenti
- Uniformante per coloritura successiva
- Facile da applicare.
-

IMPIEGO

Utilizzato per supporti murali interni o esterni particolarmente sfarinanti e dall



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992
MADE IN ITALY - UN 1263 PAINT



Applicazioni consigliate: a pennello.

Condizioni dell



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992
MADE IN ITALY - UN 1263 PAINT



Family: BUILDING

Product: ROYALFIX

DESCRIPTION

Alkali-resistant consolidating primer with high penetration for exteriors and interiors; particularly suitable for all wall supports such as gypsum, plasterboard, lime smoothing, lime and / or cement based civil plaster, paints based on organic binders (Quarzi), silicates, siloxanes and limes; reduces and uniformes the absorption of the support, ensuring a perfect anchorage and uniformity of the color of the subsequent hands of the finishing products.

Appearance of dried film: transparent

MAIN FEATURES

- Consolidating pulverization
- Piercing
- Uniforming of absorptions
- Uniforming for subsequent coloring
- Easy to apply

USE

Used for particularly crumbling interior or exterior wall supports with high absorption, ROYALFIX improves the brushing and adhesion of subsequent coatings. ROYALFIX eases the homogeneity of color for wall surfaces restored with lime or stucco patches, and thanks to the high penetration in the interstices, it facilitates the obtaining of the desired thicknesses with water-based paints, also increasing the roofing. ROYALFIX requires dilution with 400% water for internal use and 300% for external use. Appearance of dried film: transparent. Do not apply the product on surfaces treated with highly washable paints.

APPLICATION

The surface to be painted with ROYALFIX must be prepared with suitable treatment, namely:

ON NEW SUPPORTS (STUCCO or MALTA): on exterior after plastering (minimum 30/40 days), apply one coat with a diluted 300% brush with water. After 24 hours continue with the application cycle.

Inside, dilute 400% with water and apply after 24 hours from the laying of the grout. After 24 hours continue with the application cycle.

ON EXPRESSED FRAMES FREE OF PAINTING: on the outside, brush carefully with a wire brush; wash with a low pressure washer and allow the surface to dry well. Apply one coat with a diluted 300% brush with water. After 24 hours continue with the application cycle.

Inside, grout and sand if necessary. Clean the wall with a damp sponge, and apply a coat of ROYALFIX diluted 400% with water. After 24 hours continue with the application cycle.

ON ALREADY PAINTED SUPPORTS: both inside and outside make sure that the existing painting is worn out and crumbling. Do not use ROYALFIX on recently treated surfaces with highly washable water-based paints or enamels. If the pre-existing paints exfoliate, remove them, plaster and patch them where necessary.

For outdoor use, dilute ROYALFIX with 300% water and apply one coat to complete drying of the wall; after 24 hours continue with the application cycle.

Inside, dilute 400% with water and apply a coat of ROYALFIX; after 24 hours continue with the application cycle.



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992
MADE IN ITALY - UN 1263 PAINT



Recommended applications: with a brush.

Environmental and support conditions:

The substrate must be dry, free of dust, grease and any other pollutant

Room temperature: min. 10 ° C / max 35 ° C

Relative humidity of the environment: <75%

Support temperature: min. 10 ° C / max 35 ° C

DILUTION

The product is to be diluted with water 300% external use, and 400% for internal use.

STORAGE

Keep the tin tightly closed, protected from frost and sources of heat.

PHYSICAL CHARACTERISTICS (at 20 ° C and 50% - 60% U.R.)

Specific weight	1.00
-----------------	------