



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992
MADE IN ITALY - UN 1263 PAINT



Famiglia: LINEA LEGNO

Prodotto: IMPREGNANTE ALL



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992
MADE IN ITALY - UN 1263 PAINT



Comunque, in entrambi i casi, si può ottenere una ottima preparazione del supporto sostituendo il ciclo sopra descritto con
I



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992
MADE IN ITALY - UN 1263 PAINT



Family: WOOD LINE



Product: WOOD STAIN WATER BASED

DESCRIPTION

committed not film-forming, penetrates the wood fibers thoroughly protecting and enhancing the natural veins.

MAIN FEATURES

Resistant to bad weather.

Excellent Elasticity.

Excellent resistance to harsh environments (mountain, marine).

USE

On new or already painted wood, outdoors or indoors, in any environment (marine, mountain, urban, industrial), on fixtures and doors, beading, balconies, boats, etc.

Non-filmogenic product. Work by impregnation. Equipped with excellent penetration, it enhances the resistance of wood against atmospheric aggression and humidity.

The formulation guarantees a prolonged protection of the wood against the PUTREFACTION (basidiomycetes), against the BLUE STAINS (ascomycetes), and against the activity of INSECTS (worms, termites, etc.) through a combined preventive action of special components.

The presence of pigments, with extreme stability, enhances the ribbing of the wood and provides an etching in the required tone.

APPLICATION

The surface to be painted with IMPREGNANTE must be prepared with a suitable treatment, namely:

ON NEW SUPPORTS: sand and apply one or more coats of product at a distance of at least 5 hours from each other interspersed with a light sanding.

ON PAINTED SURFACES: we recommend the complete removal, after sanding or stripper. The product must be applied on bare wood.

Apply one or more coats of product interspersed with light sandin

Recommended applications: brush, roller, immersion, spray, airless.

It is not advisable to apply exclusively the NEUTRAL IMPREGNANT to the outside: in fact, with regard to UV rays, the types of IMPREGNATE PIGMENTATED offer greater resistance.

The application of the IMPREGNANTE can be renewed over time without the need for sanding, but by making the new application a thorough cleaning.

However, in both cases, an excellent preparation of the substrate can be obtained by substituting the above described cycle with the application of several preparative coatings of IMPREGNANTE, neutral or colored according to need, to be followed by ONE or MORE finishing hands of FLATTING.



Quality Management System certified ISO 9001: 2015 by Intertek

Prodotto da: **TIXE srl** - 15060 CAPRIATA D'ORBA (AL) ITALY
Via C. Ferrari, 49 (Frazione Pratalborato) - T. +39 0143 46397
www.tixepaint.com - mail@tixepaint.com - P.IVA 01779800992
MADE IN ITALY - UN 1263 PAINT



If you want to obtain an opaque (satin) finish, proceed to the penultimate hand according to the instructions on applying FLATTING.

For the last coat use the VARNISH FLATTING OPAQUE, which is perfectly compatible with the GLAZING FLATTING VARNISH, and / or with the IMPREGNANTE used for the preparation cycle.

Environmental and support conditions:

The substrate must be dry, free from dust, grease and any other pollutant

Room temperature: min. 10 ° C / max 35 ° C

Relative humidity of the environment: <75%

Support temperature: min. 10 ° C / max 35 ° C

DILUTION

The product is to be used as it is.

An accurate mixing of the BEFORE product and DURING the APPLICATION is recommended, in order to guarantee the constant homogeneity of the product.

SHADES

NEUTRAL, DOUGLAS, CHESTNUT, MOGAN, CHERRY, LIGHT WALNUT, DARK WALNUT, WENGHE ', OAK, WHITE.
(The perfect miscibility allows to obtain other intermediate shades desired)

STORAGE

In a cool and well-ventilated environment.

Keep the tin tightly closed, overturned and protected from frost and heat sources.

PHYSICAL CHARACTERISTICS

(at 20 ° C and 50% - 60% U.R.)

Specific weight 0.95 ± 0.02 kg / l.

Yield (*) 9-11 m² / l.

Drying 1 hour dry to touch

5 hours deep down

Storage life At least 36 months

(*) The yield depends on the nature and porosity of the surface.

VOC CLASSIFICATION

Wood paint and impregnating for interior / exterior finishes. VOC limit value (2010) 130. This product contains a maximum of 100 VOCs.

PRECAUTIONS

In addition to the risk and precautionary signs that regulate IMPREGNANTE in the form of production and which are shown on the container, it is recommended, before applying the product, to consult the relative SAFETY DATA SHEET. However, it is good practice to use protective gloves and goggles, and to apply it in a well-ventilated area.